

SIZING GUIDELINES

For correct system sizing, please refer to the water flow requirements of the ice machine. Water flow requirements will vary from one manufacturer to the next on the same sized machine. Variations in water quality or pressure may reduce overall water flow especially as filters are in service for prolonged periods.

SFES PRO Ice Machine Filters provide excellent sediment filtration, chlorine removal and mineral scale control. The gallon capacity ratings of the filters are based solely on chlorine removal and not scale control. Recommended filter change interval is 6 months based on the useful life of the scale control component.

CARTRIDGE		SINGLE	TWIN	TRIPLE	QUAD
SDS-10	Chlorine Capacity Gals.	N/A	N/A	N/A	N/A
	Service Flow GPM	1.75	3.5	5.25	7.00
SDS-16	Chlorine Capacity Gals.	N/A	N/A	N/A	N/A
	Service Flow GPM	2.00	4.00	6.00	8.00
TOS-10	Chlorine Capacity Gals.	10,000	20,000	30,000	40,000
	Service Flow GPM	1.75	3.5	5.25	7.00
TOS-16	Chlorine Capacity Gals.	15,000	30,000	45,000	60,000
	Service Flow GPM	2.00	4.00	6.00	8.00
TOSF-10	Chlorine Capacity Gals.	7,500	15,000	22,500	30,000
	Service Flow GPM	1.50	3.00	4.50	6.00
TOSF-16	Chlorine Capacity Gals.	10,000	20,000	30,000	40,000
	Service Flow GPM	2.00	4.00	6.00	8.00
Connection Size		3/8" MPT 3/8" FPT 3/8" QD	1/2" MPT	1/2" MPT	1/2" MPT
Min / Max Operating Pres.		20psi / 125psi	20psi / 125psi	20psi / 125psi	20psi / 125psi
Min / Max Operating Temp.		35 F / 100 F	35 F / 100 F	35 F / 100 F	35 F / 100 F
Dimensions 10" / H" x W" x D"		15.25 x 4 x 4	15.25 x 9.25 x 4	15.25 x 14 x 4	15.25 x 19 x 4
Dimensions 16" / H" x W" x D"		20.85 x 4 x 4	20.85 x 9.25 x 4	20.85 x 14 x 4	20.85 x 19 x 4