

SIZING GUIDELINES

The sizing guidelines are based on water flow requirements of coffee/tea equipment with average water pressure and water quality. Variations in water quality or pressure may reduce water flow especially as filters are in service for prolonged periods.

SFES PRO Coffee/Tea/Esspresso filters provide excellent sediment filtration, chlorine removal and mineral scale control. The gallon capacity ratings of the filters are based solely on chlorine removal and not scale control. Recommended filter change interval is 6 months based on the useful life of the scale control component.

CARTRIDGE		SINGLE	TWIN	TRIPLE	QUAD
TOS-10	Capacity Gallons Chlorine	10,000	20,000	30,000	40,000
	Service Flow GPM	1.75	3.5	5.25	7.00
TOS-16	Capacity Gallons Chlorine	15,000	30,000	45,000	60,000
	Service Flow GPM	2.00	4.00	6.00	8.00
TOSF-10	Capacity Gallons Chlorine	7,500	15,000	22,500	30,000
	Service Flow GPM	1.50	3.00	4.50	6.00
TOSF-16	Capacity Gallons Chlorine	10,000	20,000	30,000	40,000
	Service Flow GPM	2.00	4.00	6.00	8.00
Connection Size		3/8" MPT 3/8" FPT 3/8" QD	1/2" MPT	1/2" MPT	1/2" MPT
Min / Max Operating Pres.		20psi / 125psi	20psi / 125psi	20psi / 125psi	20psi / 125psi
Min / Max Operating Temp.		35 F / 100 F	35 F / 100 F	35 F / 100 F	35 F / 100 F
Dimensions 10" / H" x W" x D"		15.25 x 4 x 4	15.25 x 9.25 x 4	15.25 x 14 x 4	15.25 x 19 x 4
Dimensions 16" / H" x W" x D"		20.85 x 4 x 4	20.85 x 9.25 x 4	20.85 x 14 x 4	20.85 x 19 x 4