

SIZING GUIDELINES

For correct system sizing, please refer to the water flow requirements of the equipment. Variations in water quality or pressure may reduce overall water flow especially as filters are in service for prolonged periods.

SFES PRO Beverage Filters provide excellent sediment filtration, chlorine and chloramine removal. Recommended filter change interval is 6 months based.

CARTRIDGE		SINGLE	TWIN	TRIPLE	QUAD
TO-10	Capacity Gallons Chlorine	10,000	20,000	30,000	40,000
	Service Flow GPM	1.75	3.5	5.25	7.00
TO-16	Capacity Gallons Chlorine	15,000	30,000	45,000	60,000
	Service Flow GPM	2.00	4.00	6.00	8.00
TOC-10	Capacity Gallons Chloramine	3,500	7,000	10,500	14,000
	Service Flow GPM	1.50	3.0	4.5	6.00
TOC-16	Capacity Gallons Chloramine	5,000	10,000	15,000	20,000
	Service Flow GPM	2.00	4.00	6.00	8.00
TOF-10	Capacity Gallons Chlorine	7,500	15,000	22,500	30,000
	Service Flow GPM	1.50	3.00	4.50	6.00
TOF-16	Capacity Gallons Chlorine	10,000	20,000	30,000	40,000
	Service Flow GPM	2.00	4.00	6.00	8.00
Connection Size		3/8" MPT 3/8" FPT 3/8" QD	1/2" MPT	1/2" MPT	1/2" MPT
Min / Max Operating Pres.		20psi / 125psi	20psi / 125psi	20psi / 125psi	20psi / 125psi
Min / Max Operating Temp.		35 F / 100 F	35 F / 100 F	35 F / 100 F	35 F / 100 F
Dimensions 10" / H" x W" x D"		15.25 x 4 x 4	15.25 x 9.25 x 4	15.25 x 14 x 4	15.25 x 19 x 4
Dimensions 16" / H" x W" x D"		20.85 x 4 x 4	20.85 x 9.25 x 4	20.85 x 14 x 4	20.85 x 19 x 4